

# ET 3960 WAX TREAT PREMIUM

## FLOW IMPROVER, DETERGENT, WASA, CETANE, LUBRICITY, & MOISTURE CONTROL

**ET 3960 WAX TREAT PREMIUM** is a third generation fuel cold flow improver that contains a special water de-icer and unique wax dispersant that keeps the wax in suspension. This unique additive helps prevent large wax build-up at the bottom of the tank. Bio-diesel fuels may require a stronger treatment ratio as they are typically harder to treat fuels.

**ET 3960 WAX TREAT PREMIUM** will improve the filterability of most fuels by 30% over conventional flow improvers. Cold weather start is always a problem because of the wax that has settled to the bottom, which is drawn straight into fuel filters. Most fuel improvers cannot overcome this high concentration of settled wax, which quickly coats fuel filters.

**ET 3960 WAX TREAT PREMIUM** disperses this wax evenly throughout the fuel which allows the flow improver to break up the wax crystals into smaller particles to vastly improve filterability. Operability is improved by as much as 8° F over conventional flow improvers.

**ET 3960 WAX TREAT PREMIUM** provides L10 and XUD9 detergency at 1-2000 treat levels and DW10 and IDID detergency at 1-1000.

### *Formulated for Ultra Low Sulfur Diesel Fuels & Bio-Diesel Fuels*

#### USER BENEFITS

- Anti-gel agent improves low temperature filterability of the fuel
- Proprietary blend of Cold Flow Improvers and Heavy Wax Modifiers to maximize cold weather operability
- Flex treat ratio allows for high or low detergency levels
- Detergency to clean injectors and restore power loss due to engine build up
- Replaces lubricity level of sulfur lost in hydro treating process
- Results superior to a 70/30 #1 blend
- Less power loss due to over-blended fuels
- Disperses readily in fuels
- Detergency and stabilizer additives help reduce breakdown of bio blended products that can form particulates and block filters
- Use at 1-2000 treat levels for legacy L10 and XUD9 detergent levels and at 1-1000 for HPCR DW10 and IDID detergent levels
- Compatible with bio-diesel fuel and blends
- Moisture Control/Anti-Icer eliminates water problems
- Increases Cetane

#### TREATMENT RATIOS

|               |   |
|---------------|---|
| <b>1-2000</b> | 1 gallon treats 2000 gallons of diesel fuel<br><br>(L10, XUD9 detergency)             |
| <b>1-1000</b> | 1 gallon treats 1000 gallons of diesel fuel<br><br>(L10, XUD9, DW10, IDID detergency) |

#### CONTAINER SIZES

⇒2.5GAL, Drums and Totes

**MEETS AND EXCEEDS JOHN DEERE &  
STANADYNE REQUIREMENTS FOR ADDED  
LUBRICITY IN ULTRA LOW SULFUR DIESEL FUELS**

**THIS PRODUCT DOES NOT CONTAIN ALCOHOL**